



Main Features

- For corrosive gasses and liquids
- Class 1 according to EN 837-1
- Wetted parts Stainless steel (MEX) or Monel (MEM)
- Lloyds Register Approval
- Option : liquid-filled for applications with pulsations or vibrations
- Option : case material 1.4404 (316L) for aggressive atmosphere

Applications

- Food & Beverage
- Laboratory & Medical
- Oil & Gas / Chemical
- Water & Waste water
- Energy
- Transportation & Logistics
- Machinery

Technical Data

Nominal size	100 mm
Measurement range	MEX : -1 ... 0 to 0 ... 1600 bar MEM : -1 ... 0 to 0 ... 600 bar
Pressure limitation	
Ranges ≤ 600 bar	Steady : 100% of full scale value Fluctuating : 90% of full scale value Short time : 130% of full scale value
Ranges > 600 bar	Steady : 75% of full scale value Fluctuating : 65% of full scale value Short time : 100% of full scale value
Accuracy	Class 1 (according EN837-1)
Protection rating	IP 65 (EN 60529)
Process Connection	MEX : Stainless steel 1.4404 (AISI 316L) MEM : Monel 400
Bourdon tube	MEX : Stainless steel 1.4404 (AISI 316L) MEM : Monel 400
Case	Stainless steel 1.4301 (AISI 304) Option : Stainless steel 1.4404 (AISI 316L)

Bezel ring	Stainless steel 1.4301 (AISI 304) Option : stainless steel 1.4404 (AISI 316L)
Movement	Stainless steel
Window	Instrument glass
Window gasket	Elastomer
Dial	Aluminium, white
Pointer	Aluminium, black
Temperature	Ambient : -20 ... +70°C Medium : -40 ... +200°C (not filled) For liquid filled version see ordering details. The case temperature must not exceed +70°C Storage : -40 ... +70°C
Thermal drift	± 0.4% F.S. / 10 K (reference : 20°C)
Safety	S1 according EN837-1 Pressure gauge with blow-out device

Options


ATEX II2GDc-IM2c (Including window laminated safety glass)	Code 0078
Adjustable micro metric pointer (P ≥ 1.6 bar)	Code 0678
Adjustable friction pointer	Code 0679
Window laminated safety glass	Code 0751
Window polycarbonate	Code 0753
Blow out disc at the back	Code 0760
Restrictor screw Ø 0.5 (for fittings > 1/4")	Code 0771
Stainless steel 1.4404 (AISI 316L) solid drawn Bourdon tube	Code 0816
Lloyd's Register approval	Code 0827
Accuracy class 0.6 (For pressure gauge not filled and P < 1000 bar)	Code 0840

To be ordered separately


Material certificate 3.1 EN10204	Code Q1229
Calibration certificate EN837-1 (5 points raising and 5 points falling)	Code Q1070

INGENIERIA SCANDIMEX LIMITADA
 Av. Lib. B. O'Higgins 240, Of.81, Stgo. - Chile
 Tel.: *(56) 2 2222 1576 FFax: (56) 2 2222 2745
 info@scandimex.cl // www.scandimex.cl


Dimensions - Types of mounting




A (11)*




B (32)*




D (10)*



E (31)*



F (30)*



G (33)*

Weight (kg)
Filled : 0.81
Unfilled : 0.51

Panel cut-outs for types B and G = Ø 102 mm
*Type of mounting according to EN837-1 in brackets

mm	A	B	C	D	E	F	J	K	L	M	P	R	S	Z
NS 100	101	67	134	118	21.5	17	5.5	54.5	44.5	64	99	50.5	22	31.5

Pressure ranges

Code	Bar
B58	-0.6 ... 0
B59	-1 ... 0
B72	-1 ... 0.6
B74	-1 ... 1.5
B76	-1 ... 3
B77	-1 ... 5
B79	-1 ... 9
B81	-1 ... 15
B82	-1 ... 24
B12	0 ... 0.6
B15	0 ... 1
B16	0 ... 1.6
B18	0 ... 2.5
B19	0 ... 4
B20	0 ... 6
B22	0 ... 10
B24	0 ... 16
B26	0 ... 25
B27	0 ... 40
B29	0 ... 60
B31	0 ... 100
B33	0 ... 160
B35	0 ... 250
B38	0 ... 400
B39	0 ... 600
B41	0 ... 1 000
B42	0 ... 1 600

Code	kPa
D58	-60 ... 0
D59	-100 ... 0
D72	-100 ... 60
D74	-100 ... 150
D76	-100 ... 300
D77	-100 ... 500
D79	-100 ... 900
D81	-100 ... 1 500
D82	-100 ... 2 400
D12	0 ... 60
D15	0 ... 100
D16	0 ... 160
D18	0 ... 250
D19	0 ... 400
D20	0 ... 600
D22	0 ... 1 000
D24	0 ... 1 600
D26	0 ... 2 500
D27	0 ... 4 000
D29	0 ... 6 000
D31	0 ... 10 000
D33	0 ... 16 000
D35	0 ... 25 000
D38	0 ... 40 000
D39	0 ... 60 000

Code	kg/cm²
F58	-0.6 ... 0
F59	-1 ... 0
F72	-1 ... 0.6
F74	-1 ... 1.5
F76	-1 ... 3
F77	-1 ... 5
F79	-1 ... 9
F81	-1 ... 15
F82	-1 ... 24
F12	0 ... 0.6
F15	0 ... 1
F16	0 ... 1.6
F18	0 ... 2.5
F19	0 ... 4
F20	0 ... 6
F22	0 ... 10
F24	0 ... 16
F26	0 ... 25
F27	0 ... 40
F29	0 ... 60
F31	0 ... 100
F33	0 ... 160
F35	0 ... 250
F38	0 ... 400
F39	0 ... 600
F41	0 ... 1 000
F42	0 ... 1 600

Code	psi
H59	-30" Hg ... 0
H73	-30" Hg ... 15
H75	-30" Hg ... 30
H2C	-30" Hg ... 60
H78	-30" Hg ... 100
H79	-30" Hg ... 150
H81	-30" Hg ... 220
H82	-30" Hg ... 300
H13	0 ... 10
H15	0 ... 15
H1C	0 ... 20
H17	0 ... 30
H19	0 ... 60
H21	0 ... 100
H22	0 ... 160
H23	0 ... 200
H25	0 ... 300
H26	0 ... 400
H27	0 ... 600
H30	0 ... 1 000
H31	0 ... 1 500
H34	0 ... 3 000
H38	0 ... 6 000
H40	0 ... 10 000
H41	0 ... 15 000
H1D	0 ... 20 000

Ordering details MEX5 - MEM5

	5	-			.	xxx	/
Model							
(All stainless steel pressure gauge)	(MEX)						
Pressure gauge with monel Bourdon tube ⁽¹⁾	MEM						
Nominal size							
(100 mm)	(5)						
		-					
Type of mounting							
Stainless steel case and bezel ring 1.4301 (AISI 304)							
Bottom connection, 3 back lugs fixing				A			
Back connection, front flange, 3 mounting holes				B			
Bottom connection				D			
Back connection, 3 back lugs fixing				E			
Back connection				F			
Back connection with clamp				G			
Stainless steel case and bezel ring 1.4404 (AISI 316L)							
Bottom connection, 3 back lugs fixing				1			
Back connection, front flange, 3 mounting holes				2			
Bottom connection				(4)			
Back connection, 3 back lugs fixing				5			
Back connection				6			
Back connection with clamp				7			
Process connection							
G 1/4				2			
G 1/2				(3)			
G 3/8				J			
1/4 NPT				5			
1/2 NPT				6			
3/8 NPT				S			
M20 x 1.5				9			
Liquid filling							
Dry				0			
BH1: low viscosity glycerin/water 86% (medium : -20 ... +70 °C) ⁽²⁾				(1)			
BH2: high viscosity glycerin 99.5% (medium : 0 ... +90 °C) ⁽²⁾				2			
BH3: silicone oil (medium : -40 ... +100 °C) ⁽²⁾				3			
Unit of measurement / Pressure ranges ⁽³⁾							
(bar)						(Bxx)	
psi						Hxx	
kPa						Dxx	
MPa						Exx	
mbar						Nxx	
kg/cm²						Fxx	
bar / psi (double scale)						Kxx	
psi / bar (double scale)						Sxx	
psi / kPa (double scale)						Vxx	
kPa / psi (double scale)						Wxx	
kg/cm² / psi (double scale)						5xx	
Options to be added behind the / (see example below)							

(▶ **Standard version**)

⁽¹⁾ Monel version is not available for pressure ranges x39, x41 and x59

(2) Pressure range 0.6 bar: accuracy cl. 2.5 with BH1 and BH3, not available with BH2

⁽³⁾ Available standard pressures ranges, see tables on page 2. For ranges not listed, please contact Baumer.

Ordering example with options

MEX	5	-	B	6	0	.	S22	/	0078	-	0771	-	0679
-----	---	---	---	---	---	---	-----	---	------	---	------	---	------

All stainless steel pressure gauge
 Nominal size 100 mm
 Back connection, front flange, 3 mounting holes, case material 1.4301
 Process connection 1/2 NPT
 No liquid filling
 Double scale psi/bar ANSI : 0 ... 160 psi / 0 ... 10 bar
 Option : ATEX Version with laminated safety glass included
 Option : Restrictor screw Ø 0.5
 Option : Adjustable friction pointer